

**M8 x 30 Cup Head Nut & Bolt**



**Product**

Standard bolt length 30mm (available 20-60mm)

**Specifications**

Standard surface finish available for Securemax® M8 x 30 Cup Head Nut & Bolt is hot dip galvanised.  
Bolts are available with a painted head  
Securemax® M8 Nuts are manufactured to AS 1112.1-2000 (ISO metric hexagon nuts).  
Securemax® M8 x 30 Cup Head Bolts are manufactured to AS 1110.1 2000 (ISO metric hexagon bolts and screws).  
Galvanised to AS/NZS 4680:2006 (Hot-dipped galvanised (zinc) coatings on fabricated ferrous articles).

**Rear Security Washer**



**Product**

The Rear Security Washer is designed to clamp over the top of the 358 mesh wires and lock down onto a flat surface. This design specifically prevents the spreading or dislodgement of the welded mesh around the fixings. Therefore, the only way to remove the fixing is to cut the wires.

**Specifications**

Standard surface finish available for Securemax® Rear Security Washer's is hot dip galvanised.  
Washers are available Powder Coated  
Galvanised to AS/NZS 4680:2006 (Hot-dipped galvanised (zinc) coatings on fabricated ferrous articles).

**Shear Nut**



**Product**

Shear Nuts are a temper resistant security nut. Comprising of a hexagon portion and domed portion. When the appropriate torque loading is reached the hexagon portion shears off leaving a tamper resistant dome which cannot be removed using conventional tools.

**Specifications**

M8-14F Shear Nut with a breaking strain of 9-14ftLbs  
Manufactured from mild steel and then mechanically galvanised and passivated  
Tapped oversize 10thousands of an inch after galvanising

**Self Drilling Security Screw**




**Product**


Self Drilling Security Screws are tamper proof and require a Security Head Socket to be installed and subsequently, undone. These socket's are itemised and managed by ASF, making them the ultimate security fixing.

**Specifications**


6.5mm thread on the outside diameter x 25mm long  
Securemax® Self Drilling Screws are available hot dip galvanised.



M8 x 30 Bolt, Shear Nut & Security Washer



M8 x 30 Bolt, Std Nut & Security Washer



Self Drilling Security Screw

The specifications and descriptions of products and services contained in this data sheet were correct at the time of publishing. ASF reserves the right to change specifications or withdraw products without notice.

