

# ASF SECUREMAX® CROCTOP®

High Security Fence Toppings



## Design

CrocTop® Spiked Fence Toppings have been designed as a low cost option for deterring would be intruders from climbing over a fence or barrier. CrocTop® is machine punched to form a 25mm high triangular spike. CrocTop® is available in 2.4m lengths of flat strip or angle to suit most applications. Barbed tape toppings can also be added onto CrocTop®. Barbed tapes can be fixed at variable spacings as required.

CrocTop® Fence Toppings maintain security to the edge of mesh fencing system as they prevent the mesh sheets from being removed. Securemax® mesh panels can be raked to suit site conditions using the CrocTop® Spiked Fence Toppings.

## Performance & Durability

All CrocTop® Spiked Fence Toppings can be retrofitted to brick walls, colourbond fencing, chain wire fences and can be used as part of the Securemax® 358 and Corromesh® 358 fencing systems.

## Finishes

CrocTop® is available in a standard pre-gal finish (most common application) however, it is available in a wide variety of RAL PC colours to suit colourbond fencing.

## Recommended Fixings

Recommended fastenings of CrocTop® Spiked Fence Toppings is as simple as a standard roofing/tek screw application ranging from 20mm to 50mm screws in both standard GAL or PC finish.

## Appropriate Standards

CrocTop® Spiked Fence Toppings hot dip galvanising process is AS / NZS 4680-2006 ensuring a quality longterm non-corrosive surface finish.

## Specifications

Flat CrocTop® manufactured from 1.5 x 1200 x 1200mm Z275 galvanised sheet

Product length: 2415mm

80 spikes per length

30mm centre to centre of spikes

Available in wide variety of RAL PC colours upon request

