

ASF SECUREMAX® CROCTOP®

High Security Mesh



Design

CrocTop® Spiked Fence Toppings have been designed as a low cost option for deterring would be intruders from climbing over a fence or barrier. CrocTop® is machine punched to form a 25mm high triangular spike. CrocTop® is available in 2.4m lengths of flat strip or angle to suit most applications. Barbed tape toppings can also be added onto CrocTop®. Barbed tapes can be fixed at variable spacings as required.

CrocTop® Fence Toppings maintain security to the edge of mesh fencing system as they prevent the mesh sheets from being removed. Securemax® mesh panels can be raked to suit site conditions using the CrocTop® Spiked Fence Toppings.

Performance & Durability

All CrocTop® Spiked Fence Toppings can be retrofitted to brick walls, colourbond fencing, chain wire fences and can be used as part of the Securemax® 358 fence system.

Finishes

CrocTop® is available in pre galvanised and hot dipped galvanised finishes although powder coating and wet paint finishes are available upon request.

Recommended Fixings

Recommended fastenings of CropTop® Spiked Fence Toppings to 358 mesh and Securemax® 'H' sections via M8 cup head bolt. Securemax® washer with hexagon nut and / or shear nut. Other fastening methods are via a security self-drilling fastener to hollow sections.

Appropriate Standards

CrocTop® Spiked Fence Toppings hot dip galvanising process is AS / NZS 4680-2006 ensuring a quality longterm non-corrosive surface finish.

Specifications

- Std CrocTop® manufactured from 350 grade 50 x 50 x 4mm hot dipped galvanised equal angle
- Flat CrocTop® manufactured from 1.5 x 1200 x 1200mm Z275 galvanised sheet
- Product length: 2415mm
- 80 spikes per length
- 30mm centre to centre of spikes

