

ASF Razar Tape®

BTO 10 550GF



Design

BTO10 550mm diameter Flat Loop consists of individual loops of barb tape, ready to attach directly onto the top of an existing fence or gate.

Quality & Testing

BTO 10 550 GF is manufactured using high quality galvabond blade material, ensuring a quality surface finish.

Performance & Durability

BTO 10 550 GF is manufactured with high quality galvabond G2 strip with a short barb format formed around a high tensile galvanised spring wire. The clips used adjacently around the circumference of the barb tape are

Finishes

Standard surface finish for the Razar Tape® material is galvabond G2 strip with a spangled appearance.

Specifications

The short size blade is manufactured from 0.55mm thick Galvabond G2 strip with a blade length of 10mm at 25mm spacings, creating medium security benefits. The core wire selected is a high quality 2.5mm diameter W05 galvanised Range 1 spring wire.



Recommended Fixings

Recommended fastenings of the BTO 10 550 GF are ASF Razar Wire clips with a M8 cuphead bolt, washer and hexagon nut. ASF recommend that at every third fastening point, a shear nut is used in place of a hexagon nut.

Appropriate Standards

The BTO 10 550 GF galvabond steel is AS1397:2001. The Range 1 wire is supplied as to AS1472-2003.

