

# ASF Razar Tape®

BTO 22 600SC



## Design

BTO22 600mm diameter is made up of continuous circular coil loops alternately clipped adjacently around the circumference creating a concertina format.

## Quality & Testing

BTO 22 600 is manufactured using high quality stainless steel blade material, ensuring a quality surface finish.

## Performance & Durability

BTO 22 600 is manufactured with high quality Grade 304 stainless steel with a medium barb format formed around a high tensile galvanised wire. The clips used adjacently around the circumference of the barb tape are high quality stainless steel.

## Finishes

Standard surface finish for the Razar Tape® material is 2B Grade 304 stainless steel within a matte to satin appearance.

## Specifications

The medium size blade is manufactured from 0.55mm thick coil stainless steel with a blade length of 22mm over the points, formed at 34mm pitches by x 15mm wide, creating medium security benefits. The core wire selected is a high quality 2.5mm diameter W05 galvanised Range 1 spring wire.



## Recommended Fixings

Recommended fastenings of the BTO 22 600 are ASF Razar Wire clips with a M8 cuphead bolt, washer and hexagon nut. ASF recommend that at every third fastening point, a shear nut is used in place of a hexagon nut.

## Appropriate Standards

The BTO 22 600 stainless steel is ASTM-A240 as well as the clip. The Range 1 wire is supplied as to AS1472-2003.

